

SPECIFICATIONS

STANDARD FEATURES

SAFETY/SECURITY

4-wheel power disc brakes with Anti-lock Brake System (ABS)
 Airbags¹ – Driver and right-front passenger
 Alert chimes – Headlamps-on, key-in-ignition and door ajar
 Belt-Minder[®] safety belt reminder
 Brake/shift interlock (with automatic transmission)
 Child-safety seat top tether anchors (Regular Cab front passenger and all rear seating positions)
 Fuel pump inertia shutoff switch
 Height-adjustable safety belts – Front outboard positions
 Passenger airbag deactivation switch (Regular Cab, SuperCab)
 Safety belt energy-management retractors – Front outboard positions
 SecurILock[®] passive anti-theft ignition system
 Side-intrusion door beams

MECHANICAL

5.4L 3-valve SOHC Triton[®] V8 engine (F-350 SRW)
 6.8L 3-valve SOHC Triton V10 engine (F-350 DRW/F-450/F-550)
 6-speed manual overdrive transmission with Power TakeOff (PTO) provision (F-350/F-450; PTO obstructed by catalyst placement on 5.4L engine; 6.8L engine with manual transmission may require exhaust pipe re-routing to fit aftermarket PTO)
 Auxiliary springs – Rear
 Battery saver
 Engine block heater
 Fail-safe engine cooling system (gas engines)
 Fuel tank – 151-litre (33.2-gallon) aft-of-axle
 Manual 4-wheel-drive system with manual locking hubs (4x4 models only)
 Power steering
 Stabilizer bar – Front and rear
 Stainless steel exhaust system (major components)
 Stationary Elevated Idle Control (SEIC)²
 Steering damper
 Trailer wiring – 7-wire harness with relays, blunt cut

INTERIOR

Air conditioning
 Assist and ride handles
 Coat hooks – 1 (Regular Cab), 2 in rear of cab (SuperCab and Crew Cab)
 Dome light (front and rear with Crew Cab)
 Flip-open rear quarter windows (SuperCab)
 Instrumentation – Engine-hour meter, speedometer, tachometer, trip odometer, voltmeter (manual transmission), oil pressure, coolant temperature, transmission temperature gauge (automatic transmission), air filter minder (diesel only), fuel gauge, indicator lights and turbo boost (diesel only)
 Power points – 2 on instrument panel (including lighter)
 Upfitter switches (4) – Located on instrument panel

EXTERIOR

Bumpers – Front step
 Front fender mouldings with integrated mud flaps (F-450/F-550)
 Roof clearance lamps
 Solar-tinted glass
 Tow hooks – 2 in front
 Windshield wipers – Intermittent

¹Always wear your safety belt and always deactivate the passenger airbag when using a rear-facing child-safety seat with Regular Cab and SuperCab models. Always wear your safety belt and always secure children in the rear seat.

²Final-stage manufacturer must supply control switches.

FEATURES & OPTIONS

			XL
			XLT
			LARIAT
			MECHANICAL
●	●	●	5.4L 3-valve SOHC Triton V8 engine (F-350 only)
●	●	●	6.8L 3-valve SOHC Triton V10 engine
○	○	○	6.4L OHV 32-valve Power Stroke [®] V8 Turbo Diesel engine
○	○	○	TorqShift [®] 5-speed automatic overdrive transmission
○	○	○	Electronic Shift-On-the-Fly (ESOF) 4-wheel-drive system with auto/manual locking hubs (4x4 models only)
●	●	—	17" argent-painted steel wheels – 6 (F-350 DRW)
—	○	●	17" forged polished-aluminum wheels – 4 (F-350 DRW)
●	—	—	18" argent-painted steel wheels – 4 (F-350 SRW)
—	●	—	18" chrome-clad steel wheels – 4 (F-350 SRW)
—	○	—	18" forged polished-aluminum wheels – 4 (F-350 SRW)
—	—	●	18" premium polished-aluminum wheels – 4 (F-350 SRW)
●	●	—	19.5" argent-painted steel – 6 (F-450/F-550)
—	○	●	19.5" forged polished-aluminum wheels – 4 (F-450/F-550)
●	●	●	LT275/65R18 all-season BSW tires – 4 (F-350 SRW 4x2)
●	●	●	LT275/70R18 all-season BSW tires – 4 (F-350 SRW 4x4)
○	○	○	LT275/70R18 all-terrain BSW tires – 4 (F-350 SRW 4x4)
—	○	○	LT275/70R18 all-terrain OWL tires – 4 (F-350 SRW 4x4)
●	●	●	LT245/75R17 all-season BSW tires – 6 (F-350 DRW)
○	○	○	LT245/75R17 all-terrain BSW tires – 6 (F-350 DRW)
—	○	○	LT245/75R17 all-terrain OWL tires – 4 (F-350 DRW) ³
●	●	●	225/70R19.5 all-season BSW tires – 6 (F-450/F-550) (4x4 only)
●	●	●	225/70R19.5 steer BSW tires – 6 (F-450/F-550) (standard on 4x2, optional on 4x4)
○	○	○	225/70R19.5 traction BSW tires – 4 rear only (F-450/F-550)
○	○	○	225/70R19.5 max-traction BSW tires – 6 (F-450/F-550) ⁴ (4x4 only)
—	○	●	Advanced Security Group – Includes autolamp, autolock (automatic transmission only), illuminated-entry system, remote keyless-entry system with 2 key fobs and driver-door entry keypad
○	○	○	Alternator – Single, extra-heavy-duty 200-amp (diesel engine only)
○	○	○	Alternators – Dual, 320-amp total (diesel engine only)
○	○	○	Fuel tank – 72-litre (15.8-gallon) capacity midship in place of standard (DRW models only with some exclusions)
●	●	●	Fuel tank – 233-litre (49.1-gallon) capacity dual tank combination; 151-litre (33.2-gallon) aft-of-axle standard plus 72-litre (15.8-gallon) midship (DRW models with diesel engine only)
○	○	○	Higher-ratio rear axle (excludes 6.8L- and 6.4L-equipped SRW models)
○	○	○	Limited-slip rear axle
○	○	○	Power TakeOff (PTO) provision – Automatic transmission with 6.8L or 6.4L engines
○	○	○	Skid plate – Transfer case (SuperCab and Crew Cab 4x4 models only)
○	○	○	Spare tire and wheel – Includes jack
○	○	○	TowCommand Integrated Trailer Brake Controller (electric trailer brakes only)
○	○	○	Traction Control
○	○	○	Vehicle jack
			SEATING
●	—	—	Front reclining seat – HD vinyl
●	—	—	Front reclining seat – HD vinyl with integrated armrest
○	—	—	Front reclining seat – HD cloth
○	—	—	Front reclining seat – HD cloth with integrated armrest
○	●	●	Front seat – 40/20/40 split with armrest, cupholders and storage bin (XL – HD vinyl or HD cloth; XLT – cloth; LARIAT – leather-trimmed)
○	—	—	Front bucket seats – HD vinyl
○	—	—	Front bucket seats – HD cloth
—	○	—	Front cloth captain's chairs with centre console (requires automatic transmission)
—	—	○	Front leather-trimmed captain's chairs with centre console (requires automatic transmission)
—	●	●	Heated seats – Driver and front passenger, 2 settings
—	●	●	Lumbar support – Driver and front passenger
—	○	●	6-way power driver seat (and front-passenger seat on SuperCab and Crew Cab)
●	●	●	Rear fold-up bench seat (SuperCab and XL Crew Cab)
—	●	●	Rear FlexFold™ 60/40 split fold-flat seat, steel loadfloor, bag hooks, dual integrated cupholders and tray, and 2 outboard head restraints (Crew Cab)

● Standard ● Select Availability ○ Optional — Not Available

³Inner tire is all-terrain BSW. ⁴Not recommended for over-the-road application.

FEATURES & OPTIONS (continued)

			XL
			XLT
			LARIAT
			INTERIOR
●	●	●	Accessory delay for power features ⁵
—	—	●	Air conditioning — Dual-zone Electronic Automatic Temperature Control (EATC)
●	—	—	AM/FM stereo with digital clock and 2 speakers
○	●	●	AM/FM stereo/single-CD player with MP3 capability, digital clock and 4 speakers
—	○	○	AM/FM stereo/6-disc in-dash CD changer with MP3 capability, digital clock and 4 speakers (includes leather-wrapped steering wheel with audio controls on XLT)
—	○	○	Audiophile [®] AM/FM stereo/6-disc in-dash CD changer with MP3 capability, digital clock and 8 speakers with subwoofer (includes leather-wrapped steering wheel with audio controls on XLT; not available with Navigation System)
—	—	○	Navigation System with Audiophile AM/FM stereo/6-disc in-dash CD changer with MP3 capability, digital clock and 8 speakers with subwoofer
●	●	○	Satellite Radio (requires CD, not available on Regular Cab)
●	●	●	Auxiliary audio input jack (requires CD, not available with dual diesel tank option)
○	—	—	Radio delete
○	●	●	Cruise control (requires tilt steering wheel)
—	—	●	Enhanced message centre — Message centre, plus trip computer with compass, distance to empty, average fuel economy, autolamp configuration and status, system check, and language selection
●	—	—	Floor covering — Black vinyl
—	●	●	Floor covering — Colour-coordinated carpet
—	●	●	Floor mats — Colour-coordinated carpeted
—	○	○	Floor mats — Black all-weather
●	○	—	Carpet delete (not available with all-weather floor mats on XLT)
●	●	—	Instrument cluster — Black with black gauges
—	—	●	Instrument cluster — Metallic-faced with cream gauges
●	●	—	Mirror — Day/night rearview
—	—	●	Mirror — Auto-dimming rearview
—	—	●	Overhead console — Includes sunglasses storage and garage door opener storage
—	○	○	Power-adjustable brake and accelerator pedals (with auto. trans. only)
●	●	●	Power door locks ⁵
●	●	●	Power windows with one-touch-down driver-side feature ⁵
○	○	○	Rapid-Heat Supplemental Cab Heater (requires diesel engine with air conditioning, alternator upgrade and TorqShift)
○	●	●	Steering wheel — Tilt (requires cruise control)
●	●	—	Steering wheel — Black urethane
—	—	●	Steering wheel — Colour-coordinated leather-wrapped with secondary audio/climate controls
●	●	—	Visors with passenger mirror
—	—	●	Visors with illuminated mirrors
—	—	●	Woodgrain-style instrument panel accents
			EXTERIOR
●	—	—	Bumper — Front step, Black-painted
●	●	●	Bumper — Front step, chrome-steel
○	○	●	Cab steps — Black-moulded
●	—	—	Grille — Black-painted
—	●	●	Grille — Chrome with Medium Platinum insert
●	—	—	Headlamps — Sealed-beam halogen
○	●	●	Headlamps — Dual-beam jewel-effect ⁶
●	●	●	Lamp — Underhood engine compartment ⁶
●	—	—	Mirrors — Manually telescoping trailer tow with 2-way fold and manual glass
●	●	—	Mirrors — Manually telescoping trailer tow with 2-way fold, power/heated glass, manual spotter mirrors and integrated clearance lamps and turn signals
—	—	●	Mirrors — PowerScope [™] power-telescoping/folding trailer tow with power/heated glass, manual spotter mirrors and integrated clearance lamps and turn signals
—	○	●	Privacy glass (rear doors and rear window, XLT requires sliding rear window)
○	○	●	Sliding rear window — Manual

EQUIPMENT PACKAGES

			XL
			XLT
			LARIAT
○	○	○	15,000-lb. (6804-kg) GVWR Package (F-450)
○	○	○	AmbulancePrep Package ⁷ (requires diesel engine)
○	—	—	Onvenience Package — Includes cruise control, tilt steering wheel, air conditioning, and AM/FM stereo with single-CD player and digital clock
—	—	○	DriverMemory Package — Includes memory for trailer tow mirrors, power driver seat and power-adjustable pedals (requires power-adjustable pedals)
○	○	○	Heavy-Service Suspension Package ⁸ — Includes 1-up heavy-service front springs; not available if maximum spring is computer selected
○	○	○	Extra-Heavy-Service Suspension Package ⁸ — Includes 2-up extra-heavy-service front springs; not available if maximum spring is computer selected
○	○	○	High-Capacity Trailer Tow Package (F-450/F-550 with diesel engine) — Includes 12,701-kg (28,000-lb.) GCWR with F-450/F-550 6-speed manual transmission; 13,608-kg (30,000-lb.) GCWR with F-450 with TorqShift; and 14,969-kg (33,000-lb.) GCWR with F-550 with TorqShift and upgraded 4.88 rear axle gear set
○	○	○	LowDeflection Package — Recommended for rear-biased loading [F-450/F-550 only; excludes 3576-mm (140.8") wheelbase]
○	○	○	PayloadUpgrade Package — Increases GVWR for increased payload range (F-350 SRW and F-550 only)
●	●	●	PowerEquipment Group — Includes power locks, mirrors and front windows (plus rear on Crew Cab) with one-touch-down driver-side feature and accessory delay (requires air conditioning on XL) (XL Fleet only)
○	○	○	SnowPlow Prep Package ⁸ — Includes specific spring/GAWR upgrade ranging from 2359–3175 kg (5200–7000 lbs.) (depending on model), 200-amp alternator and unique fan clutch with 6.4L diesel (4x4 only on F-350)
○	○	●	TrailerTow Prep Package — Includes trailer brake wiring kit
○	—	—	XLDécor Group — Includes chrome-steel bumpers; dual-beam jewel-effect headlamps; bright chrome hub covers and centre ornaments (SRW only); underhood engine compartment lamp

⁷Restrictions and special instructions apply. See your Ford of Canada Dealer for information.

⁸Option and other restrictions apply. See your Ford of Canada Dealer for information.

ENGINES

	5.4L 3-VALVE TRITON V8 SOHC	6.8L 3-VALVE TRITON V10 SOHC	6.4L POWER STROKE V8 TURBO DIESEL OHV (32-Valve)
Type			
Fuel injection	Sequential Electronic	Sequential Electronic	High-Pressure Common-Rail
Engine control system	Electronic	Electronic	Electronic
Induction system	Specially tuned	Specially tuned	Series Sequential Turbochargers, intercooler
Battery	12-volt; 650-CCA/72-amp	12-volt; 650-CCA/72-amp	Dual 12-volt; 750-CCA/78-amp
Alternator	115-amp	115-amp	135-amp (Single 200-amp or dual combined 320-amp opt.)
Cooling system	Pressurized series flow	Pressurized series flow	Pressurized series flow
Cylinders	8	10	8
Cylinder-head material	Aluminum	Aluminum	Cast iron
Block material	Cast iron	Cast iron	Cast iron
Valve operation	Hydraulic roller	Hydraulic roller	Push rod/rocker arms
Camshaft drive	Variable cam timing	Silent chain	Gear
Bore mm (in.)	90 (3.55)	90 (3.55)	98 (3.86)
Stroke	106 (4.16)	106 (4.16)	105 (4.13)
Compression ratio	9.8:1	9.2:1	16.7:1
Horsepower (hp @ rpm)	300 @ 5000	362 @ 4750	350 @ 3000 (F-350) 325 @ 3000 (F-450/F-550)
Torque (lb.-ft. @ rpm)	365 @ 3750	457 @ 3250	650 @ 2000 (F-350) 600 @ 2000 (F-450/F-550)
Recommended fuel	Unleaded	Unleaded	Ultra-Low-Sulfur Diesel

⁹Included as part of Power Equipment Group on XL. (Fleet only.)

⁶Included as part of the XL Décor Group.

Audiophile is a registered trademark of Audiophile, Inc.

SPECIFICATIONS

MAXIMUM LOADED TRAILER WEIGHT RATINGS kg (lbs.)

MANUAL TRANSMISSION

REGULAR CAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW ¹	F-350 4x4 DRW ¹
5.4L 3-valve Triton® V8	3.73	6804 (15,000)	3810 (8400)	3583 (7900)	3674 (8100)	3447 (7600)
	4.10	7711 (17,000)	4717 (10,400)	4491 (9900)	—	—
6.8L 3-valve Triton V10	4.10	7938 (17,500)	—	—	4808 (10,600)	4581 (10,100)
		9072 (20,000)	6033 (13,300)	5806 (12,800)	—	—
	4.30	9299 (20,500)	—	—	6123 (13,500)	5897 (13,000)
6.4L Power Stroke® V8 Turbo Diesel	3.73	10,433 (23,000)	7031 (15,500)	6804 (15,000)	—	—
	4.10	10,206 (22,500)	—	—	7031 (15,500)	6804 (15,000)
		10,659 (23,500)	—	—	7076 (15,600)	6895 (15,200)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW ¹	F-450 4x4 SRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8301 (18,300)	8119 (17,900)	8255 (18,200)	8119 (17,900)
	5.38	11,793 (26,000)	8301 (18,300)	8119 (17,900)	8255 (18,200)	8119 (17,900)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7938 (17,500)	7756 (17,100)	—	—
	4.88	11,793 (26,000)	7938 (17,500)	7756 (17,100)	7893 (17,400)	7711 (17,000)
		12,701 (28,000) ²	8845 (19,500)	8664 (19,100)	8800 (19,400)	8618 (19,000)

SUPERCAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW
5.4L 3-valve Triton V8	3.73	6804 (15,000)	3629 (8000)	3447 (7600)	—	—
	4.10	7711 (17,000)	4536 (10,000)	4354 (9600)	—	—
6.8L 3-valve Triton V10	4.10	9072 (20,000)	5851 (12,900)	5625 (12,400)	—	—
		9299 (20,500)	—	—	5942 (13,100)	5715 (12,600)
	4.30	10,206 (22,500)	—	—	6849 (15,100)	6622 (14,600)
6.4L Power Stroke V8 Turbo Diesel	3.73	10,433 (23,000)	6849 (15,100)	6622 (14,600)	—	—
	4.10	10,659 (23,500)	—	—	6940 (15,300)	6713 (14,800)
		10,659 (23,500)	—	—	6940 (15,300)	6713 (14,800)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW	F-450 4x4 SRW	F-550 4x2 DRW	F-550 4x4 DRW
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8119 (17,900)	7938 (17,500)	8074 (17,800)	7938 (17,500)
	5.38	11,793 (26,000)	8119 (17,900)	7938 (17,500)	8074 (17,800)	7938 (17,500)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7756 (17,100)	7575 (16,700)	—	—
	4.88	11,793 (26,000)	7756 (17,100)	7575 (16,700)	7711 (17,000)	7575 (16,700)
		12,701 (28,000) ²	8664 (19,100)	8482 (18,700)	8618 (19,000)	8482 (18,700)

CREW CAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW
5.4L 3-valve Triton V8	3.73	6804 (15,000)	3583 (7900)	3311 (7300)	—	—
	4.10	7711 (17,000)	4491 (9900)	4218 (9300)	—	—
6.8L 3-valve Triton V10	4.10	9072 (20,000)	5761 (12,700)	5534 (12,200)	—	—
		9299 (20,500)	—	—	5851 (12,900)	5625 (12,400)
	4.30	10,206 (22,500)	—	—	6759 (14,900)	6532 (14,400)
6.4L Power Stroke V8 Turbo Diesel	3.73	10,433 (23,000)	6759 (14,900)	6532 (14,400)	—	—
	4.10	10,659 (23,500)	—	—	6849 (15,100)	6622 (14,600)
		10,659 (23,500)	—	—	6849 (15,100)	6622 (14,600)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW ¹	F-450 4x4 SRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8029 (17,700)	7893 (17,400)	8029 (17,700)	7847 (17,300)
	5.38	11,793 (26,000)	8029 (17,700)	7893 (17,400)	8029 (17,700)	7847 (17,300)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7666 (16,900)	7484 (16,500)	—	—
	4.88	11,793 (26,000)	7666 (16,900)	7484 (16,500)	7666 (16,900)	7484 (16,500)
		12,701 (28,000) ²	8573 (18,900)	8391 (18,500)	8573 (18,900)	8391 (18,500)

¹F-350 DRW/F-450/F-550 weights shown are for 3581-mm (141") wheelbase Regular Cab or 4470-mm (176") wheelbase Crew Cab models. For 4191-mm (165"), 4801-mm (189"), 5080-mm (200") and 5105-mm (201") wheelbase models, weights may be somewhat less [usually not more than 90.8 kg (200 lbs.), or 181.4 kg (400 lbs.) with 5105-mm (201") wheelbase].

²Available with High-Capacity Trailer Tow Package only.

AUTOMATIC TRANSMISSION

REGULAR CAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW ¹	F-350 4x4 DRW ¹
5.4L 3-valve Triton V8	3.73	7257 (16,000)	4264 (9400)	4037 (8900)	—	—
	4.10	7484 (16,500)	—	—	4354 (9600)	4128 (9100)
6.8L 3-valve Triton V10		4.10	8165 (18,000)	5171 (11,400)	4944 (10,900)	—
	8165 (18,000)		—	—	5262 (11,600)	5035 (11,100)
	4.30	9525 (21,000)	6486 (14,300)	6260 (13,800)	—	—
6.4L Power Stroke V8 Turbo Diesel	3.73	10,433 (23,000)	7031 (15,500)	6804 (15,000)	—	—
	4.10	10,206 (22,500)	—	—	7076 (15,600)	6895 (15,200)
		10,659 (23,500)	—	—	7076 (15,600)	6895 (15,200)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW ¹	F-450 4x4 SRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8301 (18,300)	8119 (17,900)	8255 (18,200)	8119 (17,900)
	5.38	11,793 (26,000)	8301 (18,300)	8119 (17,900)	8255 (18,200)	8119 (17,900)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7938 (17,500)	7756 (17,100)	7893 (17,400)	7711 (17,000)
	4.88	11,793 (26,000)	7938 (17,500)	7756 (17,100)	7893 (17,400)	7711 (17,000)
		13,608 (30,000) ²	9752 (21,500)	9525 (21,000)	—	—
		14,969 (33,000) ²	—	—	11,068 (24,400)	10,886 (24,000)

SUPERCAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW
5.4L 3-valve Triton V8	3.73	7257 (16,000)	4082 (9000)	3901 (8600)	—	—
	4.10	8165 (18,000)	4990 (11,000)	4808 (10,600)	—	—
6.8L 3-valve Triton V10	4.10	9525 (21,000)	6305 (13,900)	6078 (13,400)	—	—
		9752 (21,500)	—	—	6396 (14,100)	6169 (13,600)
	4.30	10,433 (23,000)	—	—	7076 (15,600)	6849 (15,100)
6.4L Power Stroke V8 Turbo Diesel	3.73	10,433 (23,000)	6849 (15,100)	6622 (14,600)	—	—
	4.10	10,659 (23,500)	—	—	6940 (15,300)	6713 (14,800)
		10,659 (23,500)	—	—	6940 (15,300)	6713 (14,800)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW	F-450 4x4 SRW	F-550 4x2 DRW	F-550 4x4 DRW
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8119 (17,900)	7938 (17,500)	8074 (17,800)	7938 (17,500)
	5.38	11,793 (26,000)	8119 (17,900)	7938 (17,500)	8074 (17,800)	7938 (17,500)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7756 (17,100)	7575 (16,700)	7711 (17,000)	7575 (16,700)
	4.88	11,793 (26,000)	7756 (17,100)	7575 (16,700)	7711 (17,000)	7575 (16,700)
		13,608 (30,000) ²	9571 (21,100)	9389 (20,700)	—	—
		14,969 (33,000) ²	—	—	10,886 (24,000)	10,750 (23,700)

CREW CAB

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW
5.4L 3-valve Triton V8	3.73	7257 (16,000)	4037 (8900)	3765 (8300)	—	—
	4.10	8165 (18,000)	4944 (10,900)	4672 (10,300)	—	—
6.8L 3-valve Triton V10	4.10	9525 (21,000)	6214 (13,700)	5987 (13,200)	—	—
		9752 (21,500)	—	—	6305 (13,900)	6078 (13,400)
	4.30	10,433 (23,000)	—	—	6985 (15,400)	6759 (14,900)
6.4L Power Stroke V8 Turbo Diesel	3.73	10,433 (23,000)	6759 (14,900)	6532 (14,400)	—	—
	4.10	10,659 (23,500)	—	—	6849 (15,100)	6622 (14,600)
		10,659 (23,500)	—	—	6849 (15,100)	6622 (14,600)

ENGINE	AXLE RATIO	GCWR kg (lbs.)	F-450 4x2 SRW ¹	F-450 4x4 SRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
6.8L 3-valve Triton V10	4.88	11,793 (26,000)	8029 (17,700)	7893 (17,400)	8029 (17,700)	7847 (17,300)
	5.38	11,793 (26,000)	8029 (17,700)	7893 (17,400)	8029 (17,700)	7847 (17,300)
6.4L Power Stroke V8 Turbo Diesel	4.30	11,793 (26,000)	7666 (16,900)	7484 (16,500)	7666 (16,900)	7484 (16,500)
	4.88	11,793 (26,000)	7666 (16,900)	7484 (16,500)	7666 (16,900)	7484 (16,500)
		13,608 (30,000) ²	9480 (20,900)	9299 (20,500)	—	—
		14,969 (33,000) ²	—	—	10,841 (23,900)	10,659 (23,500)

Note: 5th-wheel trailer weights shown. See your Ford of Canada Dealer for conventional trailer weights.

Note: Trailer weights shown assume 454-kg (1000-lb.) second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed listed GCWR. Trailer kingpin weight should be 15–25% of total loaded trailer weight. Make sure that the vehicle payload (reduced by option weight) will accommodate trailer kingpin weight and the weight of passengers and cargo added to the towing vehicle. The addition of trailer kingpin weight, and the weight of passengers and cargo cannot cause vehicle weights to exceed the rear GAWR (Gross Axle Weight Rating) or GVWR (Gross Vehicle Weight Rating). These ratings can be found on the vehicle's Compliance Label.

WEIGHTS & DIMENSIONS

REGULAR CAB											
	F-350 SRW	F-350 DRW	F-350 DRW	F-450 DRW	F-450 DRW	F-450 DRW	F-450 DRW	F-450 DRW	F-550 DRW	F-550 DRW	F-550 DRW
Wheelbase mm (in.)	3576 (140.8)	3576 (140.8)	4186 (164.8)	3576 (140.8)	4186 (164.8)	4796 (188.8)	5100 (200.8)	3576 (140.8)	4186 (164.8)	4796 (188.8)	5100 (200.8)
Cab-to-axle mm (in.)	1524 (60)	1524 (60)	2134 (84)	1524 (60)	2134 (84)	2743 (108)	3048 (120)	1524 (60)	2134 (84)	2743 (108)	3048 (120)
Max. GVWR											
4x2 kg (lbs.)	4853 (10,700)	5897 (13,000)	5897 (13,000)	7257 (16,000)	7257 (16,000)	7257 (16,000)	7257 (16,000)	8142 (17,950)	8618 (19,000)	8142 (17,950)	8618 (19,000)
4x4 kg (lbs.)	4990 (11,000)	5897 (13,000)	5897 (13,000)	7257 (16,000)	7257 (16,000)	7257 (16,000)	7257 (16,000)	8142 (17,950)	8618 (19,000)	8142 (17,950)	8618 (19,000)
Max. payload											
4x2 kg (lbs.)	2132 (4700)	3279 (7230)	3243 (7150)	4259 (9390)	4214 (9290)	4091 (9020)	4069 (8970)	5121 (11,290)	5529 (12,190)	4953 (10,920)	5380 (11,860)
4x4 kg (lbs.)	2059 (4540)	3066 (6760)	3030 (6680)	4096 (9030)	4051 (8930)	3924 (8650)	3901 (8600)	4958 (10,930)	5366 (11,830)	4785 (10,550)	5216 (11,500)
Overall length mm (in.)	5740 (226)	5740 (226)	6350 (250)	5740 (226)	6350 (250)	6960 (274)	7264 (286)	5740 (226)	6350 (250)	6960 (274)	7264 (286)
Top of cab to ground – Empty											
4x2 mm (in.)	1943 (76.5)	1948 (76.7)	1941 (76.4)	2017 (79.4)	2017 (79.4)	2014 (79.3)	2012 (79.2)	2022 (79.6)	2019 (79.5)	2017 (79.4)	2014 (79.3)
4x4 mm (in.)	2032 (80.0)	2037 (80.2)	2032 (80.0)	2017 (79.4)	2017 (79.4)	2014 (79.3)	2012 (79.2)	2022 (79.6)	2019 (79.5)	2017 (79.4)	2014 (79.3)
Top of frame to ground – Empty											
4x2 mm (in.)	800 (31.5)	815 (32.1)	810 (31.9)	828 (32.6)	828 (32.6)	826 (32.5)	823 (32.4)	838 (33.0)	836 (32.9)	833 (32.8)	831 (32.7)
4x4 mm (in.)	838 (33.0)	826 (32.5)	851 (33.5)	828 (32.6)	828 (32.6)	826 (32.5)	823 (32.4)	838 (33.0)	836 (32.9)	833 (32.8)	831 (32.7)
Width between frame rails mm (in.)	866 (34.1)	866 (34.1)	866 (34.1)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)
Axle clearance mm (in.)	203 (8.0)	196 (7.7)	196 (7.7)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)
Front tread width mm (in.)	1735 (68.3)	1735 (68.3)	1735 (68.3)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)
Rear tire outside width mm (in.)	2022 (79.6)	2342 (92.2)	2342 (92.2)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)

SUPERCAB				
	F-350 SRW	F-350 DRW	F-450 DRW	F-550 DRW
Wheelbase mm (in.)	4110 (161.8)	4110 (161.8)	4110 (161.8)	4110 (161.8)
Cab-to-axle mm (in.)	1524 (60)	1524 (60)	1524 (60)	1524 (60)
Max. GVWR				
4x2 kg (lbs.)	4990 (11,000)	5897 (13,000)	7257 (16,000)	8142 (17,950)
4x4 kg (lbs.)	5171 (11,400)	5897 (13,000)	7257 (16,000)	8142 (17,950)
Max. payload				
4x2 kg (lbs.)	2100 (4630)	3044 (6710)	4091 (9020)	4953 (10,920)
4x4 kg (lbs.)	2068 (4560)	2835 (6250)	3924 (8650)	4785 (10,550)
Overall length mm (in.)	6274 (247)	6274 (247)	6274 (247)	6274 (247)
Top of cab to ground – Empty				
4x2 mm (in.)	1951 (76.8)	1958 (77.1)	2024 (79.7)	2029 (79.9)
4x4 mm (in.)	2037 (80.2)	2042 (80.4)	2024 (79.7)	2029 (79.9)
Top of frame to ground – Empty				
4x2 mm (in.)	795 (31.3)	810 (31.9)	828 (32.6)	836 (32.9)
4x4 mm (in.)	836 (32.9)	851 (33.5)	828 (32.6)	836 (32.9)
Width between frame rails mm (in.)	866 (34.1)	866 (34.1)	866 (34.1)	869 (34.2)
Axle clearance mm (in.)	203 (8.0)	196 (7.7)	201 (7.9)	201 (7.9)
Front tread width mm (in.)	1735 (68.3)	1735 (68.3)	1900 (74.8)	1900 (74.8)
Rear tire outside width mm (in.)	2022 (79.6)	2342 (92.2)	2385 (93.9)	2385 (93.9)

CREW CAB						
	F-350 SRW	F-350 DRW	F-450 DRW	F-450 DRW	F-550 DRW	F-550 DRW
Wheelbase mm (in.)	4475 (176.2)	4475 (176.2)	4475 (176.2)	5085 (200.2)	4475 (176.2)	5085 (200.2)
Cab-to-axle mm (in.)	1524 (60)	1524 (60)	1524 (60)	2134 (84)	1524 (60)	2134 (84)
Max. GVWR						
4x2 kg (lbs.)	5080 (11,200)	5897 (13,000)	7257 (16,000)	7257 (16,000)	8142 (17,950)	8142 (17,950)
4x4 kg (lbs.)	5216 (11,500)	5897 (13,000)	7257 (16,000)	7257 (16,000)	8142 (17,950)	8142 (17,950)
Max. payload						
4x2 kg (lbs.)	2109 (4650)	2962 (6530)	4010 (8840)	3937 (8680)	4872 (10,740)	4799 (10,580)
4x4 kg (lbs.)	2077 (4580)	2835 (6250)	3846 (8480)	3769 (8310)	4708 (10,380)	4631 (10,210)
Overall length mm (in.)	6640 (261.4)	6640 (261.4)	6640 (261.4)	7249 (285.4)	6640 (261.4)	7249 (285.4)
Top of cab to ground – Empty						
4x2 mm (in.)	1966 (77.4)	1971 (77.6)	2037 (80.2)	2035 (80.1)	2042 (80.4)	2037 (80.2)
4x4 mm (in.)	2050 (80.7)	2055 (80.9)	2037 (80.2)	2035 (80.1)	2040 (80.3)	2037 (80.2)
Top of frame to ground – Empty						
4x2 mm (in.)	792 (31.2)	808 (31.8)	826 (32.5)	826 (32.5)	833 (32.8)	833 (32.8)
4x4 mm (in.)	833 (32.8)	848 (33.4)	826 (32.5)	826 (32.5)	826 (32.5)	833 (32.8)
Width between frame rails mm (in.)	866 (34.1)	866 (34.1)	869 (34.2)	869 (34.2)	869 (34.2)	869 (34.2)
Axle clearance mm (in.)	203 (8.0)	196 (7.7)	201 (7.9)	201 (7.9)	201 (7.9)	201 (7.9)
Front tread width mm (in.)	1735 (68.3)	1735 (68.3)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)
Rear tire outside width mm (in.)	2022 (79.6)	2342 (92.2)	2385 (93.9)	2385 (93.9)	2385 (93.9)	2385 (93.9)

Load rating represents maximum allowable weight of people, cargo and body equipment and is reduced by the weight of optional equipment.

INTERIOR DIMENSIONS

	REG. CAB	SUPERCAB	CREW CAB
FRONT			
Head room mm (in.)	1052 (41.4)	1052 (41.4)	1052 (41.4)
Shoulder room mm (in.)	1727 (68.0)	1727 (68.0)	1727 (68.0)
Hip room mm (in.)	1717 (67.6)	1717 (67.6)	1717 (67.6)
Leg room mm (in.)	1041 (41.0)	1041 (41.0)	1041 (41.0)
REAR			
Head room mm (in.)	—	975 (38.4)	1052 (41.4)
Shoulder room mm (in.)	—	1730 (68.1)	1730 (68.1)
Hip room mm (in.)	—	1709 (67.3)	1709 (67.3)
Leg room mm (in.)	—	808 (31.8)	1062 (41.8)

BUSINESS PREFERRED NETWORK

Each of the select dealerships in our Business Preferred Network (BPN) is committed to providing quality commercial-oriented products and service, as well as special financing and billing arrangements, to businesses that rely on Ford products. As a BPN customer, your business vehicles receive priority service at your BPN dealership to help get your vehicle back on the road quickly.



FINANCIAL SERVICES

Our commercial purchase plans and lines of credit offer attractive rates, negotiable terms and business-friendly options. If you prefer to lease, our CommercialLeaseSM programs offer a wide variety of package options to meet your needs. For additional information, please visit our website at www.fordcredit.ca.

